

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier		
TRIM SHEEN		
MTS 0019		
ixture and uses advised against		
Car maintenance product. Dressing		
This product is not recommended for any other		
purpose than stated above.		
1.3. Details of the supplier of the safety data sheet		
Motor Trade Supplies Ltd		
Unit 5		
Preston Nurseries		
Weghill Road		
Hull		
HU12 8SX		
+44 (0) 7778 411 723		
sales@mtsproducts.co.uk		
1.4. Emergency telephone number		
+44 (0) 7778 411 723 Opening Hours 9 am - 4 pm		
(Monday - Friday)		

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture Classification (EC 1272/2008)	
Physical hazards	Flam. Liq. 2 - H225
Health hazards	STOT SE 3 - H336 Asp. Tox. 1 - H304
Environmental hazards	Aquatic Chronic 2 - H411
2.2. Label elements	
Hazard Pictograms	
<u>(!)</u>	
Signal word	Danger
Hazard statements	H225 Highly flammable liquid and vapour.
	H304 May be fatal if swallowed and enters airways.
	H336 May cause drowsiness or dizziness.

	H411 Toxic to aquatic life with long lasting effects.
Precautionary statements	P210 Keep away from heat, hot surfaces, sparks,
	open flames and other ignition sources. No smoking.
	P271 Use only outdoors or in a well-ventilated area.
	P273 Avoid release to the environment.
	P280 Wear protective gloves/ protective clothing/ eye
	protection/ face protection.
	P301+P310 IF SWALLOWED: Immediately call a
	POISON CENTER/ doctor.
	P303+P361+P353 IF ON SKIN (or hair): Take off
	immediately all contaminated clothing. Rinse skin with
	water/ shower.
	P331 Do NOT induce vomiting.
	P403+P233 Store in a well-ventilated place. Keep
	container tightly closed.
	P501 Dispose of contents/ container in accordance
	with national regulations.
Contains	Naphtha (petroleum), hydrotreated light
Supplementary precautionary statements	P240 Ground/ bond container and receiving
	equipment. P241 Use explosion-proof electrical
	equipment.
	P242 Use only non-sparking tools.
	P243 Take precautionary measures against static
	discharge.
	P261 Avoid breathing vapour/ spray.
	P304+P340 IF INHALED: Remove person to fresh air
	and keep comfortable for breathing.
	P312 Call a POISON CENTER/ doctor if you feel
	unwell.
	P370+P378 In case of fire: Use foam, carbon dioxide,
	dry powder or water fog to extinguish.
	P391 Collect spillage.
	P403+P235 Store in a well-ventilated place. Keep
	cool.
	cool.
	P405 Store locked up.
2.3. Other hazards	

SECTION 3: Composition/information on ingredients

3.1. Mixtures

Naphtha (petroleum), hydrotreated light 60-100% CAS number: EC number: 926-141-6 REACH registration number: 01- 2110473851-33 Classification Flam. Liq. 2 - H225 Classification (67/548/EEC or 1999/45/EC) Xn;R65. F;R11. N;R51/53. R67,R66. STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.4 Description of first aid massaums		
4.1. Description of first aid measures		
General information	Immediately remove any clothing soiled by the product.	
	p. comon	
Inhalation	Supply fresh air; consult doctor in case of complaints.	
Ingestion	DO NOT induce vomiting. Get medical attention immediately.	
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Seek medical attention if irritation or symptoms persist.	
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.	
4.2. Most important symptoms and effects, both acute and delayed		
Inhalation	Difficulty in breathing. Headache. Coughing, chest tightness, feeling of chest pressure. Nausea, vomiting.	
Ingestion	May cause stomach pain or vomiting. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation.	
Skin contact	Prolonged contact may cause redness, irritation and dry skin.	
4.3. Indication of any immediate medical attention and special treatment needed		
Notes for the doctor	No specific recommendations. If in doubt, get medical attention promptly.	

SECTION 5: Firefighting measures

5.1. Extinguishing media		
Suitable extinguishing media	Extinguish with the following media: Alcohol-resistant foam. Carbon dioxide or dry powder.	
Unsuitable extinguishing media	Water	
5.2. Special hazards arising from the substance or mixture		
Hazardous combustion products	Fire creates: Carbon monoxide (CO).	
5.3. Advice for firefighters		
Protective actions during firefighting	Control run-off water by containing and keeping it out	
	of sewers and watercourses. Cool containers	
	exposed to flames with water until well after the fire is	
	out.	
Special protective equipment for firefighters	Wear self-contained respiratory protective device.	

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and	d emergency procedures
Personal precautions	Wear protective clothing as described in Section 8 of
	this safety data sheet. Remove all sources of ignition.
	Ensure adequate ventilation of the working area.
	Evacuate personnel to a safe area. Wear suitable
	protective equipment.
6.2. Environmental precautions	
Environmental precautions	Avoid the spillage or runoff entering drains, sewers or
	watercourses. If substance has entered a water
	course or sewer or contaminated soil or vegetation,
	advise the appropriate authorities.
6.3. Methods and material for containment and clea	ning up
Methods for cleaning up	Absorb spillage with non-combustible, absorbent
• •	material. Do not use sawdust or other combustible
	material. For waste disposal, see Section 13.
6.4. Reference to other sections	, , , , , , , , , , , , , , , , , , ,
Reference to other sections	See Section 7 for information on safe handling.
	See Section 8 for information on personal protection
	· ·
Methods for cleaning up 6.4. Reference to other sections	advise the appropriate authorities. ning up Absorb spillage with non-combustible, absorbent material. Do not use sawdust or other combustible material. For waste disposal, see Section 13. See Section 7 for information on safe handling.

SECTION 7: Handling and storage

7.1. Precautions for safe handling		
Usage precautions	Container must be kept tightly closed when not in use. Ensure adequate ventilation of the working area. Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Protect from heat.	
7.2. Conditions for safe storage, including any incompatibilities		
Storage precautions	Avoid contact with oxidising agents. Avoid acids. Keep container tightly closed. Avoid direct sunlight. Do not store near heat sources or expose to high temperatures. Keep away from sources of ignition - No smoking. Protect against electrostatic charges.	
Storage class	Flammable liquid storage.	
7.3. Specific end use(s)		
Specific end use(s)	The identified uses for this product are detailed in Section 1.2.	

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters Occupational exposure limits	
Naphtha (petroleum), hydrotreated light	
DNEL	Consumer - Oral; Long term systemic effects: 699 mg/kg/day Consumer - Dermal; Long term systemic effects: 699 mg/kg/day Industry - Dermal; Long term systemic effects: 773 mg/kg/day Consumer - Inhalation; Long term systemic effects: 608 mg/m3 Industry - Inhalation; Long term systemic effects: 2035 mg/m3

8.2. Exposure controls

Protective equipment







Eye/face protection	Wear tightly sealed goggles
Hand protection	Impermeable material. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Suitable gloves: Nitrile rubber, NBR Fluorocarbon rubber (Viton)
Hygiene measures	Based on and limited to our experience of this product, the following special advice is believed to provide satisfactory protection for the industrial user or handler. The choice of suitable protective equipment depends on work conditions and what methods are used for handling the substance. This advice is not a substitute for each Company conducting their own Risk/COSHH Assessments, but is provided as general guidance. Do not smoke in the work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Use barrier cream to prevent drying of skin. Eating, smoking and water fountains prohibited in immediate work area.
Respiratory protection	Use suitable respiratory protective device in case of insufficient ventilation. In confined or poorly ventilated areas suitable respiratory protection should be used if exposed to high levels of spray or mist.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties	
Appearance	Liquid
Colour	Clear
Odour	Cherry
Flash point	<5°C
Relative density	~ 0.8
Solubility(ies)	Insoluble in water.
9.1. Other information	
Other information	N/A

SECTION 10: Stability and reactivity

10.1. Reactivity	
Reactivity	Reacts with strong oxidising agents. Reacts with strong acids.
10.2. Chemical stability	
Stability	Stable at normal ambient temperatures and when used as recommended.
10.3. Possibility of hazardous reactions	<u>s</u>
Stability	May react with strong oxidising agents and strong acids.
10.4. Conditions to avoid	
Conditions to avoid	Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials	
Materials to avoid	Alkalis and Peroxides Strong acids.
10.6. Hazardous decomposition products	
Hazardous decomposition products	Carbon monoxide (CO). Carbon dioxide (CO2).

SECTION 11: Toxicological information

11.1. Information on toxicological effects	
Route of entry	Inhalation Ingestion. Skin and/or eye contact Refer to Section 4 of SDS for routes of exposure and corresponding symptoms.
Target organs	Respiratory system, lungs
Medical symptoms	Irritation of eyes and mucous membranes. Skin irritation.
Medical considerations	Skin disorders and allergies.
Naphtha (petroleum), hydrotreated light	
Acute toxicity - oral	
Acute toxicity oral (LD ₅₀ mg/kg)	5,000.0
Species	Rat
Acute toxicity - Dermal	
Acute toxicity dermal (LD ₅₀ mg/kg)	2,000.0
Species	Rat
Skin contact	Irritant to skin and mucous membranes.
Eye contact	No specific health hazards known.

SECTION 12: Ecological information

Eastaviaity	Toxio to aquatia arganismo, may aquas lang tarm
Ecotoxicity	Toxic to aquatic organisms, may cause long-term
	adverse effects in the aquatic environment.
12.1. Toxicity Acute aquatic toxicity	
Acute toxicity - fish	LC50, 96 hours: ~ 13.4 mg/l, Algae
Acute toxicity - aquatic invertebrates	EC50, 48 hours: ~ 3 mg/l, Daphnia magna
Acute toxicity - aquatic plants	LC50, 72 hours: ~ 10-30 mg/l, fish
12.2. Persistence and degradability	
No further relevant information available. The product is biodegradable.	
12.3. Bioaccumulative potential	
Bioaccumulative potential	No further relevant information available.
12.4. Mobility in soil	
Mobility	No further relevant information available.
12.5. Results of PBT and vPvB assessment	
Results of PBT and vPvB assessment	This product does not contain any substances
	classified as PBT or vPvB.
12.6. Other adverse effects	
Other adverse effects	Water hazard class 1 (German Regulation)
	(Assessment by list): slightly hazardous for water.
	Do not allow product to reach ground water, water
	course or sewage system. Toxic for fish, also
	poisonous for plankton in water bodies.
	1:
	Toxic for aquatic organisms.

SECTION 13: Disposal considerations

13.1. Waste treatment methods	
General Information	The packaging must be empty (drop-free when
	inverted).
Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Packaging: Recover and reclaim
	or recycle. If practical.

SECTION 14: Transport information

Special Provisions note	
<u>14.1. UN number</u>	
UN No. (ADR/RID)	1993
UN No. (IMDG)	1993
UN No. (ICAO)	1993
UN No. (ADN)	1993
14.2. UN proper shipping name	
Proper shipping name (ADR/RID)	FLAMMABLE LIQUID, N.O.S. CONTAINS NAPHTHA (PETROLEUM), HYDROTREATED LIGHT
Proper shipping name (IMDG)	FLAMMABLE LIQUID, N.O.S. CONTAINS NAPHTHA (PETROLEUM), HYDROTREATED LIGHT
Proper shipping name (ICAO)	FLAMMABLE LIQUID, N.O.S. CONTAINS NAPHTHA (PETROLEUM), HYDROTREATED LIGHT
Proper shipping name (ADN)	FLAMMABLE LIQUID, N.O.S. CONTAINS NAPHTHA (PETROLEUM), HYDROTREATED LIGHT
14.3. Transport hazard class(es)	
ADR/RID class	3
ADR/RID classification code	F1
ADR/RID label	3
IMDG class	3
ICAO class/division	3
AND class	3

Transport labels





14.4. Packing group	
ADR/RID packing group	II
IMDG packing group	II
ADN packing group	II
ICAO packing group	II
14.5. Environmental hazards	
Environmentally hazardous substance/marine pollutant	
14.6. Special precautions for user	
EmS	F-E, S-E
ADR transport category	2
Emergency Action Code	•3YE
Hazard Identification Number (ADR/RID)	33
Tunnel restriction code	(D/E)
14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code	
Transport in bulk according to Annex II of	Not applicable.
MARPOL 73/78 and the IBC Code	

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture	
National regulations	Commission Decision 2000/532/EC as amended by Decision 2001/118/EC establishing a list of wastes and hazardous waste pursuant to Council Directive 75/442/EEC on waste and Directive 91/689/EEC on hazardous waste with amendments.
EU legislation	Dangerous Preparations Directive 1999/45/EC. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16

	December 2008 on classification, labelling and
	packaging of substances and mixtures (as amended).
Guidance	Workplace Exposure Limits EH40.
	Approved Classification and Labelling Guide (Sixth
	edition) L131. Safety Data Sheets for Substances
	and Preparations.
Health and environmental listings	Regulation (EC) 689/2008 of the European
_	Parliament and of the Council of 17 June 2008
	concerning the export and import of dangerous
	chemicals (as amended).
15.2. Chemical safety assessment	
No chemical safety assessment has been carried out.	

SECTION 16: Other information

General information	PLEASE NOTE: The risk phrases itemised below are those relating to concentrated forms of the raw materials used in this product and are not necessarily applicable to the finished item. Please see Section 2 for the current classification of this product.
Revision comments	N/A
Revision date	01/10/20
Revision	1.0
Supersedes date	N/A
Risk phrases in full	R65 Harmful: may cause lung damage if swallowed.
Hazard statements in full	H225 Highly flammable liquid and vapour.
	H304 May be fatal if swallowed and enters airways.
	H336 May cause drowsiness or dizziness.
	H411 Toxic to aquatic life with long lasting effects.

The information provided in this document is based on our present state of knowledge of the product and is given in good faith and to the best of our experience. However, it should not be construed as a technical specification or as guaranteeing specific properties, accuracy, reliability or completeness. In no event we will be responsible for damages or effects of any nature whatsoever, either express or implied, resulting from the use of this information. It is the own responsibility of the consignee and the user of the product to comply with all prevailing and applicable laws, regulations and directives. They should also make their own determination as to the suitability of the product for a particular use or application by carrying out a full risk assessment of their specific processes and systems of work. All information contained within this document is for the product in its undiluted state and relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated.